



S1D13781

Power Consumption

Document Number: X94A-G-003-01

Issue Date: 2015/02/26

NOTICE

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You are requested not to use, to resell, to export and/or to otherwise dispose of the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies.

©SEIKO EPSON CORPORATION 2011-2015, All rights reserved.

Table of Contents

1	S1D13781 Power Consumption	4
2	Summary	7
3	Change Record.....	8

1 S1D13781 Power Consumption

S1D13781 power consumption is affected by many system design variables.

- Memory clock frequency (MCLK): CPU performance to memory, and other functions – the higher the frequency, the higher the performance and power consumption.
- Pixel clock frequency (PCLK): determines the LCD frame-rate – the higher the frequency, the higher the frame-rate and power consumption.
- V_{DD} voltage level: the voltage level affects power consumption – the higher the voltage, the higher the power consumption.
- Display mode: the resolution and color depth affect power consumption – the higher the resolution/color depth, the higher the power consumption.
- Layer Rotation: using a layer rotation option of either 90 or 270 degrees, will be higher power consumption than 0 or 180 degrees.
- Look Up Table: if a LUT is used, then power consumption will be higher.

The S1D13781 supports software initiated power save modes. The power consumption in power save modes is affected by various system design variables.

- Clock states during the power save mode: disabling the clocks during power save mode has substantial power savings.

1.1 Conditions

The following table provides examples of typical configurations for some 320x240 panels and their effects on power consumption. The following conditions apply.

- All tests were run with a static full color palette display.
- All tests were done using the Direct 16-bit Mode 1 host bus interface.
- All tests set the PLL/MCLK for 60MHz, from a CLKI of 24MHz.

Table 1-1: S1D13781 Total Power Consumption for 320x240 panels

Test Condition <i>COREV_{DD} and PLLV_{DD} = 1.5V and IOV_{DD} = 3.3V</i>							Current Consumption (mA)		
							S1D13781 Active		
Resolution	Panel Type	Frame Rate	Clocks (MHz) Other Consideration	Rotation	LUT	Color Depth	CORE	PLL	IO
320x240	18-bit TFT	57	CLKI = 24.0 MHz POCLK/MCLK = 60.0 MHz PCLK = MCLK / 7	0	Yes	24	3.977	0.530	2.195
		57		90	Yes	24	4.789	0.530	1.927
		0	CLKI = 24.0 MHz POCLK/MCLK = 60.0 MHz PCLK = MCLK / 7 Power Save Enabled = PSM1	0	Yes	24	2.150	0.530	0.101
		0	CLKI = STOPPED POCLK/MCLK = 0.0 MHz PCLK = MCLK / 7 Power Save Enabled = PSM0	0	Yes	24	0.005	0	0.071
	Color STN 8-bit Format 2	68		0	Yes	24	4.290	0.530	1.347
		68		90	Yes	24	5.260	0.530	1.347
	Mono STN 8-bit	70		0	Yes	8 for Mono	3.353	0.532	0.999

The following table provides an example of a 480x272 24-bit TFT panel and the effects on power consumption for specific environments. The following conditions apply.

- All tests were run with a static full color palette display, **except the test where the 2D BitBLT engine was running.**
- All tests were done using the Direct 16-bit Mode 1 host bus interface.

Table 1-2: S1D13781 Total Power Consumption for 480x272 panels

Test Condition <i>COREV_{DD} and PLLV_{DD} = 1.5V and IOV_{DD} = 3.3V</i>							Current Consumption (mA)		
Resolution	Panel Type	Frame Rate	Clocks (MHz) Other Consideration	Rotation	LUT	Color Depth	S1D13781 Active		
							CORE	PLL	IO
480x272	24-bit TFT	57	CLKI = 24.0 MHz POCLK/MCLK = 60.0 MHz PCLK = MCLK / 7	0	Yes	8	4.605	0.532	3.793
		57		0	Yes	16	3.982	0.532	2.719
		57		0	Yes	24	4.815	0.532	3.794
		57		0	No	RGB888	4.605	0.532	3.793
		57		90	Yes	24	6.201	0.532	2.556
		57	0	Yes	24	9.689	0.532	6.333	
		0	0	Yes	24	0.005	0	0.071	
			CLKI = STOPPED POCLK/MCLK = 0.0 MHz PCLK = MCLK / 7 Power Save Enabled = PSM0						

1. This test has the 2D BitBLT engine performing a constant BitBLT writes, requires a high-level of CPU activity and a rapidly updating display.

2 Summary

The system design variables in Section 1, “S1D13781 Power Consumption” and in the included comparison tables, show that S1D13781 power consumption depends on the specific implementation. When the S1D13781 is running, power consumption depends on the desired performance and LCD frame-rate. Power save mode consumption depends on the Clock state.

In a typical design environment, the S1D13781 can be configured to be an extremely power-efficient Simple LCD Controller with high performance and flexibility.

3 Change Record

X00A-G-008-01 Revision 1.3 - Issued: February 26, 2015

- Re-format.
- Changed PSM1 mode power consumption in Table 1-1: S1D13781 Total Power Consumption for 320x240 panels and changed connective LCD panels

X94A-G-003-01 Revision 1.0 - Issued: April 06, 2011

- Re-format and edit document for release

AMERICA

EPSON ELECTRONICS AMERICA, INC.

214 Devcon Drive,
San Jose, CA 95112, USA
Phone: +1-800-228-3964 FAX: +1-408-922-0238

EUROPE

EPSON EUROPE ELECTRONICS GmbH

Riesstrasse 15, 80992 Munich,
GERMANY
Phone: +49-89-14005-0 FAX: +49-89-14005-110

ASIA

EPSON (CHINA) CO., LTD.

7F, Jinbao Bldg., No.89 Jinbao St.,
Dongcheng District,
Beijing 100005, CHINA
Phone: +86-10-8522-1199 FAX: +86-10-8522-1125

SHANGHAI BRANCH

7F, Block B, Hi-Tech Bldg., 900 Yishan Road,
Shanghai 200233, CHINA
Phone: +86-21-5423-5577 FAX: +86-21-5423-4677

SHENZHEN BRANCH

12F, Dawning Mansion, Keji South 12th Road,
Hi-Tech Park, Shenzhen 518057, CHINA
Phone: +86-755-2699-3828 FAX: +86-755-2699-3838

EPSON HONG KONG LTD.

Unit 715-723, 7/F Trade Square, 681 Cheung Sha Wan Road,
Kowloon, Hong Kong.
Phone: +852-2585-4600 FAX: +852-2827-4346

EPSON TAIWAN TECHNOLOGY & TRADING LTD.

14F, No. 7, Song Ren Road,
Taipei 110, TAIWAN
Phone: +886-2-8786-6688 FAX: +886-2-8786-6660

EPSON SINGAPORE PTE., LTD.

1 HarbourFront Place,
#03-02 HarbourFront Tower One, Singapore 098633
Phone: +65-6586-5500 FAX: +65-6271-3182

SEIKO EPSON CORP. KOREA OFFICE

19F, KLI 63 Bldg., 60 Yoido-dong,
Youngdeungpo-Ku, Seoul 150-763, KOREA
Phone: +82-2-784-6027 FAX: +82-2-767-3677

SEIKO EPSON CORP. MICRODEVICES OPERATIONS DIVISION

IC Sales & Marketing Department

421-8, Hino, Hino-shi, Tokyo 191-8501, JAPAN
Phone: +81-42-587-5814 FAX: +81-42-587-5117